



SPECTRA 44 XC





SPECTRA 44 XC

Derived from the latest technologies, the Spectra 44 XC film incorporates a ceramic compound which enables it to reduce solar heat gain whilst retaining its transparent properties. Our External Spectrally Selective films (Spectra 22XC, 333XC & 44XC) are made from ceramic construction and are then considered as metal free window films.



SOLAR SCREEN® Warranty See the notice "new guarantees for the external films'



Storage from -5°C to +40°C

3 YEARS



REACH RoHS compliant RESPECTED

WIDTHS AVAILABLE:



152 cm





TECHNICAL DATASHEET

Data calculated based on film applied to clear glass 3 mm thick (*on double glazing 4-16-4)

Ultraviolet transmission	<1 %
Visible light transmission	54 %
Reflection of external visible light	14 %
Reflection of internal visible light	14 %
Total solar energy rejected	57 %
Total solar energy rejected 2*	61 %
Solar ratio:	
Solar energy reflection	10 %
Solar energy absorption	62 %
Solar energy transmission	28 %
Reduction in Solar Glare	42 %
g-value	0.42
u-value	5.08
Rejected Infrared (760-2500 nm)	+/- 97%
Shading coefficient	0.5
Installation type: Exterior	
Roll length	30,5 m
Film composition	PET
Thickness	60 μ

Colour from the outside: HIGHLY

NEUTRAL

CONSTRUCTION

- 1. "Hard" scratch resistant layer, for durability and ease of maintenance during window cleaning
- 2. High optical quality polyester with anti IR
- **3.** Bonding adhesive

- 4. High optical quality polyester5. PS adhesive, glass polymerization within 15 days6. Protection release liner, disposable after installation


INSTALLATION ADVICE

Vertical installation and on standard glass surface**

Clear single pane	~
Tinted single pane	Ĭ
Reflective tinted single pane	~
Clear double pane	Ĭ
Tinted double pane	Ĭ
Reflective tinted double pane	~
Gas-filled double pane - Low E	Ĭ
STADIP EXT. clear double pane	×
STADIP INT. clear double pane	Ī



*Recommendations provided on the basis of a glazed surface covering up to 2.5m², contact us for definitive details or to obtain a thermal chock analysis report.



MAINTENANCE INSTRUCTIONS

Soapy water solution (ref. 0805 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Tummennus (lasien tummennukset) - info@atummennus.fi tai © 040-5511417 Mainos | Paino | Sisustus | Autoteippaus - info@amainos.fi tai © 045-8025055